adapt·M

Dimensions

measures in millimeters

390







840

190

The *adapt* family is a versatile solution for the modernization of current infrastructure or urban furniture. The *adapt·M* dynamic information modules can display a large amount of information in a compact format. They allow you to install dynamic information displays with cutting edge technology almost anywhere, with a simple installation and reduced costs.

Features

- · Dual 16" electronic ink displays.
- Up to 12 lines of text simultaneously. Up to 24 characters per line.
- Notices and messages function with high resolution graphics.
- · LED display illumination.
- · Audio messages system.
- · Compatible power sources:
 - Solar energy.
 - Power grid connection.
 - Hybrid (grid connection + batteries)
- · Anti-reflective frontal safety glass.
- · Adaptable achoring system for shelters and poles*



Specifications

Power source: Photovoltaic panel * *

Installation voltage: 12V

Average power draw: 2.88W

Battery autonomy: up to 10 days * * *

Data transmission: NB-IoT, GPRS, Cat-M1

optional: 4G, 5G

Display technology: ChLCD

Display resolution: 1: 320x240px

2: 800x640px

Operation temperature: -20 to +80°C

Materials and finishes: Brushed AlSI-304

Stainless steel

Dust and water protection: IP-65

Impact resistance: IK-10

* May require additional costs.* * Sold separately.

* * * Autonomy may vary depending on the configuration.



adapt·M

Dimensions

measures in millimeters







840 190

The *adapt* family is a versatile solution for the modernization of current infrastructure or urban furniture. The *adapt·M* dynamic information modules can display a large amount of information in a compact format. They allow you to install dynamic information displays with cutting edge technology almost anywhere, with a simple installation and reduced costs.

Features

- · Wide 29.3" True Color TFT display.
- · Can display video and animations.
- · Split-screen functionality to display different kinds of information simultaneously.
- · Wireless communication via 4G, 5G or WiFi.
- · High display brightness. Outdoors ready.
- · Audio messages system.
- · Compatible power sources:
 - Power grid connection.
 - Hybrid (grid connection + batteries)
- · Anti-reflective frontal safety glass.
- Adaptable achoring system for shelters and poles*



Specifications

Power source: Power grid connection

Installation voltage: 220V

Data transmission: 4G, 5G, WiFi, Ethernet

Display technology: TFT LCD

Display resolution: 1920x710px

Display brightness: 1000 cd/m²

Color depth: 24-bit, 16.7m

Visibility angles: Horizontal: 178° Vertical: 178°

Operation temperature: -30 to +80°C

Materials and finishes: AISI-304 brushed

stainless steel

Dust and water protection: IP-65

Impact resistance: IK-10

^{*} May require additional costs.